

**NEW**

CONI DUO

CONI DUO is ideal for narrow conference and training desks and tables. CONI DUO provides simple and unimpeded access to power, media and data connections on the table or desk from two sides. There is no reduction in leg room under the desk or table.

When not in use, CONI DUO integrates fully into the surface of the desk or table. When you need power, data or media, simply open one of the two covers, plug into the desired socket and close the cover again. The brush insert prevents the cables from jamming. The harmonious appearance of an "even" table is retained. Configuration of CONI DUO data connections can be freely selected (see custom modules from page 142). Power strips can also be interchanged quickly, and at any time, without the need for tools. Integrated functionality and maximum flexibility not just for today but also for the advances of tomorrow.

The benefits at a glance

- Access from 2 opposite sides
- Just one desk or table cut-out needed
- Integrated into your desktop or tabletop
- Minimum built-in depth, robust frame design
- Integrated brush insert for closing once cables have been plugged in

CONI DUO, short and long version

The name says it all:
CONI twin pack.

Designed especially for use with
small meeting tables, which have
energy and data connections on
opposite sides.



CONI DUO built-in frame short

6-way: 2 x 3-way

Outer dimensions: approx.:
505 x 151 mm

CONI DUO built-in frame long

12-way: 2 x 6-way

Outer dimensions: approx.:
782 x 151 mm

Art. no. | Version

CONI DUO Silver grey, similar to RAL9006 **NEW**

6-way, short

911.026 | · Dimensions approx. 505 x 151 mm

12-way, long

911.025 | · Dimensions approx. 782 x 151 mm

CONI DUO White, similar to RAL9010 **NEW**

6-way, short

911.028 | · Dimensions approx. 505 x 151 mm

12-way, long

911.029 | · Dimensions approx. 782 x 151 mm








3-way power strips for CONI

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version

C **3-way: 2 x custom module + power socket outlet** **Length: approx. 217 mm**






Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug

	912.002	· 1 x socket outlet with earthing contact, shuttered, black, set at 35°
	912.009	· 1 x French / UTE socket outlet, shuttered, black, set at 35°
	912.016	· 1 x Swiss / CH socket outlet, black, set at 0°
	912.0055*	· 1 x Italian / earthing contact combination, black, set at 35°
	912.0080	· 1 x UK 3.15A individually fused, shuttered, black, set at 90°



C **3-way: 1 x custom module + power socket outlets** **Length: approx. 217 mm**


Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug

	912.003	· 2 x socket outlet with earthing contact, black, set at 35°
	912.010	· 2 x French / UTE socket outlet, shuttered, black, set at 35°
	912.015	· 3 x Swiss / CH socket outlet, black, set at 0°
	912.037*	· 1 x socket outlet with earthing contact, black, set at 35°, · 1 x Swiss / CH socket outlet, black, set at 0°
	912.045	· 2 x UK 3.15A individually fused, shuttered, black, set at 90°



C **3-way: 1 x custom module + power socket outlets, black and red** **Length: approx. 217 mm**


Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)

	912.023*	· 1 x socket outlet with earthing contact, black, set at 35° · 1 x socket outlet with earthing contact, red, set at 35°
--	----------	--



3-way: 2 x CAT5e + power socket outlets **Length: approx. 217 mm**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug

	333.1008	· 2 x socket outlet with earthing contact, black, set at 35° · 2 x CAT5e RJ45, front: socket / rear: socket
---	----------	--



3-way: Power socket outlets **Length: approx. 217 mm**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug

	333.1007	· 3 x socket outlet with earthing contact, black, set at 35°
---	----------	--



C **3-way: 3 x custom module** **Length: approx. 217 mm**

Anodised aluminium profile; without power connection




912.000	· without socket outlets
---------	--------------------------



Art. no. | Version

U **C** **3-way: 1 x USB double charger (5.2 V/2.15 A) + custom modules + power socket outlets** **Length: approx. 217 mm**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug

	912.0167	· 1 x socket outlet with earthing contact, shuttered, black, set at 35° · 1 x USB double charger (5.2 V/2.15 A), 1 x custom module
	912.0156	· 2 x socket outlet with earthing contact, shuttered, black, set at 35° · 1 x USB double charger (5.2 V/2.15 A)
	912.0171	· 1 x French / UTE socket outlet, shuttered, black, set at 35° · 1 x USB double charger (5.2 V/2.15 A), 1 x custom module



* No storage type

6-way power strips for CONI




Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version

6-way: 5 x custom module + power socket outlet Length: approx. 356 mm **C**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug
 912.004 | · 1 x socket outlet with earthing contact, shuttered, black, set at 35° 

6-way: 4 x custom module + power socket outlet Length: approx. 356 mm **C**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug
 912.005 | · 2 x socket outlet with earthing contact, shuttered, black, set at 35° 
 912.011 | · 2 x French / UTE socket outlet, shuttered, black, set at 35° 
 912.017 | · 3 x Swiss / CH socket outlet, black, set at 0° 



6-way: 3 x custom module + power socket outlet Length: approx. 356 mm **C**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug
 912.006 | · 3 x socket outlet with earthing contact, shuttered, black, set at 35° 
 912.012 | · 3 x French / UTE socket outlet, shuttered, black, set at 35° 
 912.018 | · 4 x Swiss / CH socket outlet, black, set at 0° 
 912.022 | · 3 x UK 3.15A individually fused, shuttered, black, set at 90° 


6-way: 2 x custom module + power socket outlet Length: approx. 356 mm **C**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug
 912.007 | · 4 x socket outlet with earthing contact, shuttered, black, set at 35° 
 912.013 | · 4 x French / UTE socket outlet, shuttered, black, set at 35° 
 912.019 | · 5 x Swiss / CH socket outlet, black, set at 0° 
 912.035* | · 1 x socket outlet with earthing contact, black, set at 35° 
 | · 3 x Swiss / CH socket outlet, black, set at 0° 
 912.0221 | · 4 x UK 3.15A individually fused, shuttered, black, set at 90° 


6-way: 1 x custom module + power socket outlet Length: approx. 356 mm **C**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug
 912.008 | · 5 x socket outlet with earthing contact, shuttered, black, set at 35° 
 912.014 | · 5 x French / UTE socket outlet, shuttered, black, set at 35° 
 912.021 | · 4 x UK 3.15A individually fused, shuttered, black, set at 90° 

6-way: 3 x custom module + power socket outlet, black and red Length: approx. 356 mm **C**

Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)
 912.024 | · 1 x socket outlet with earthing contact, shuttered, black, set at 35° 
 | · 2 x socket outlet with earthing contact, shuttered, red, set at 35°

6-way: 2 x custom module + power socket outlet, black and red Length: approx. 356 mm **C**





Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)
 912.025 | · 2 x socket outlet with earthing contact, black, set at 35° 
 | · 2 x socket outlet with earthing contact, red, set at 35°

6-way: 6 x custom module Length: approx. 356 mm **C**

Anodised aluminium profile; without power connection
 912.001 | · without socket outlets

Art. no. | Version

6-way: 1 x USB double charger (5.2 V/2.15 A) + custom modules + power socket outlets Length: approx. 356 mm **C U**

Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug
 912.0168 | · 2 x socket outlet with earthing contact, shuttered, black, set at 35° 
 | · 1 x USB double charger, 3 x custom module
 912.0169 | · 3 x Swiss / CH socket outlet, black, set at 90° 
 | · 1 x USB double charger, 3 x custom module
 912.0172 | · 2 x French / UTE socket outlet, shuttered, black, set at 35° 
 | · 1 x USB double charger, 3 x custom module
 912.0280 | · 2 x UK 3.15A individually fused, shuttered, black, set at 90° 
 | · 1 x USB double charger, 3 x custom module