



# CONI

Integrated functionality

Built in frame

CONI built-in frame, short and long version

The built-in depth is 56 mm, suitable for desk or table top thickness as of 10 mm. R5 corner radius facilitates flush mounting in desks or tables.

The brush strips can easily be replaced with colour strips; no tools are required. Simply remove the built-in frame from the top of the desk or table and unscrew the 3 re-usable plastic rivets.



**CONI built-in frame short**  
Outer dimensions: 248 x 151 mm  
Built-in dimensions: 237 x 139 mm

**CONI built-in frame long**  
Outer dimensions: 387 x 151 mm  
Built-in dimensions: 375 x 139 mm



Art. no.	Version	Color
<b>CONI short</b> 338.0203	· Silver-grey similar to RAL9006	<b>Silver-grey</b>

<b>CONI long</b> 338.0205	· Silver-grey similar to RAL9006	<b>Silver-grey</b>
------------------------------	----------------------------------	--------------------



<b>CONI short</b> 338.0204	· Anthracite	<b>Anthracite</b>
-------------------------------	--------------	-------------------

<b>CONI long</b> 338.0206	· Anthracite	<b>Anthracite</b>
------------------------------	--------------	-------------------



<b>CONI short</b> 338.0214	· Chrome-plated	<b>Chrome-plated</b>
-------------------------------	-----------------	----------------------

<b>CONI long</b> 338.0227	· Chrome-plated	<b>Chrome-plated</b>
------------------------------	-----------------	----------------------



<b>CONI short</b> 911.000	· Satin white RAL9010	<b>Satin white</b>
------------------------------	-----------------------	--------------------

<b>CONI long</b> 911.001	· Satin white RAL9010	<b>Satin white</b>
-----------------------------	-----------------------	--------------------



<b>CONI short</b> 911.002	· Black RAL9005	<b>Black</b>
------------------------------	-----------------	--------------

<b>CONI long</b> 911.003	· Black RAL9005	<b>Black</b>
-----------------------------	-----------------	--------------



<b>CONI short</b> 911.004	· Ground stainless steel	<b>Stainless steel</b>
------------------------------	--------------------------	------------------------

<b>CONI long</b> 911.005	· Ground stainless steel	<b>Stainless steel</b>
-----------------------------	--------------------------	------------------------

# Mounting

## CONI bracket

- For mounting CONI socket outlets without using a built-in frame, can be installed underneath the top of a desk or table in a cable tray, for example. Standard spax screws (which can be purchased from all good retailers) are required for mounting.
- Takes account of the rear-side outgoing feeder and bending radii of power and data connections.

Art. no. | Version

### CONI mounting high

918.002	<ul style="list-style-type: none"> <li>· Black</li> <li>· 2 items in plastic bag</li> <li>· Distance between socket outlet profile and floor: 30 mm distance between floor and top edge</li> <li>· Power strip: 74 mm</li> </ul>
---------	--



## CONI holder

- For optional mounting on CONI mounting frame (short and long version)
- Allows excess lengths of cable to be stowed when plugged in
- Easy to fit by hooking into mounting frame which is already fitted using the plastic rivets provided.
- Small extra built-in depth of approx. 20 mm in addition to built-in depth of mounting frame

Art. no. | Version

### CONI holder

911.910	· Version for Coni mounting frame, short
911.913	· Version for Coni mounting frame, long



## CONI brushes

Art. no. | Version

### CONI brush strip short

911.900	· Red
911.901	· Blue
911.902	· White
911.903	· Yellow
911.904	· Black

### CONI brush strip long

911.905	· Red
911.906	· Blue
911.907	· White
911.908	· Yellow
911.909	· Black



# CONI

## Power strips

See glossary for country-specific information

Supply lines and Custom Modules are available separately

Art. no.	Version
	<b>CUSTOM</b>   <b>3-way: 2x custom modules + power socket outlet</b> <span style="float: right;"><b>Length: approx. 217 mm</b></span> Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug
	 912.002   · 1 black socket outlet with earthing contact, set at 35°
	 912.009   · 1 child-proof French / UTE socket outlet, black, set at 35°
	 912.016   · 1 Swiss / CH socket outlet, black, set at 0°
	 912.0055*   · 1 Italian / earth contact combination, black, set at 35°
	<b>CUSTOM</b>   <b>3-way: 1x custom module + power socket outlets</b> <span style="float: right;"><b>Length: approx. 217 mm</b></span> Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug
	 912.003   · 2 black socket outlets with earthing contact, set at 35°
	 912.010   · 2 child-proof French / UTE socket outlets, black, set at 35°
	 912.015   · 3 Swiss / CH socket outlets, black, set at 0°
	 912,037*   · 1 black socket outlet with earthing contact, set at 35°, · 1 Swiss / CH socket outlet, black, set at 0°
	 912,045*   · 2 UK 5A individually fused, child-proof 90°
	<b>CUSTOM</b>   <b>3-way: 1x custom module + power socket outlets, black and red</b> <span style="float: right;"><b>Length: approx. 217 mm</b></span> Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)
	 912,023*   · 1 black socket outlet with earthing contact, set at 35° · 1 socket outlet with earthing contact, red, set at 35°
	<b>3-way: 2x CAT5e + power outlet sockets</b> <span style="float: right;"><b>Length: approx. 217 mm</b></span> Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug
	 333.1008   · 2 black socket outlets with earthing contact, set at 35° · 2 CAT5e RJ45, front: socket / rear: socket
	<b>3-way: Power socket outlets</b> <span style="float: right;"><b>Length: approx. 217 mm</b></span> Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug
	 333.1007   · 3 black socket outlets with earthing contact, set at 35°
	<b>CUSTOM</b>   <b>3-way: 3x custom modules</b> <span style="float: right;"><b>Length: approx. 217 mm</b></span> Anodised aluminium profile; without power connection
	912.000   without socket outlets

# Power strips

See glossary for country-specific information

Supply lines and Custom Modules are available separately

Art. no.	Version	Length: approx. 356 mm	CUSTOM	
<b>6-way: 5x custom modules + power socket outlet</b>				
Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug				
912.004	· 1 black socket outlet with earthing contact, set at 35°			
<b>6-way: 4x custom modules + power socket outlet</b>				
Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug				
912.005	· 2 black socket outlet with earthing contact, set at 35°			
912.011	· 2 child-proof French / UTE socket outlet, black, set at 35°			
912.017	· 3 Swiss / CH socket outlets, black, set at 0°			
<b>6-way: 3x custom modules + power socket outlet</b>				
Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug				
912.006	· 3 black socket outlets with earthing contact, set at 35°			
912.012	· 3 child-proof French / UTE socket outlets, black, set at 35°			
912.018	· 4 Swiss / CH socket outlets, black, set at 0°			
912,022*	· 3 UK 5A individually fused, child-proof 90°			
<b>6-way: 2x custom modules + power socket outlet</b>				
Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug				
912.007	· 4 black socket outlets with earthing contact, set at 35°			
912.013	· 4 child-proof French / UTE socket outlet, black, set at 35°			
912.019	· 5 Swiss / CH socket outlets, black, set at 0°			
912,035*	· 1 black socket outlet with earthing contact, set at 35° · 3 Swiss / CH socket outlet, black, set at 0°		 	
<b>6-way: 1x custom module + power socket outlet</b>				
Anodised aluminium profile; power input: 0.1m cable and GST18i3 plug				
912.008	· 5 black socket outlets with earthing contact, set at 35°			
912.014	· 5 child-proof French / UTE socket outlet, black, set at 35°			
912,021*	· 4 UK 5A individually fused, child-proof 90°			
<b>6-way: 1x custom module + power socket outlet, black and red</b>				
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)				
912.024	· 1 black socket outlet with earthing contact, set at 35° · 2 socket outlets with earthing contact, red, set at 35°			
<b>6-way: 2x custom module + power socket outlet, black and red</b>				
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)				
912.025	· 2 black socket outlets with earthing contact, set at 35° · 2 socket outlets with earthing contact, red, set at 35°			
<b>6-way: 6x custom module</b>				
Anodised aluminium profile; without power connection				
912.001	without socket outlets			

\* No storage type