



TOP FRAME

Perfect elegance

TOP FRAME BUILT-IN FRAME FOR MOUNTING BELOW TABLE OR DESK

· Including fixing accessories

Art. no. | Version



TOP FRAME **EV1 anodised**

Frameless, short – for 4-way power socket

925.000

- Anodised EV1 aluminium flap, black powder-coated housing
- Dimensions (L x W x H): approx. 300 x 87.5 x 98 mm



TOP FRAME **EV1 anodised**

Frameless, long – for 8-way power socket

925.001

- Anodised EV1 aluminium flap, black powder-coated housing
- Dimensions (L x W x H): approx. 482.5 x 87.5 x 98 mm



TOP FRAME **RAL 9006**

Frameless, short – for 4-way power socket

925.002

- Aluminium flap RAL 9006, black powder-coated housing
- Dimensions (L x W x H): approx. 300 x 87.5 x 98 mm



TOP FRAME **RAL 9006**

Frameless, long – for 8-way power socket

925.003

- Aluminium flap RAL 9006, black powder-coated housing
- Dimensions (L x W x H): approx. 300 x 87.5 x 98 mm

TOP FRAME BUILT-IN FRAME FOR MOUNTING ON THE TABLETOP

· Including fixing accessories

Art. no. | Version

TOP FRAME **RAL 9006**

Asymmetrical surround frame, short – for 4-way power strip
 925.500 | · Aluminium flap RAL 9006, black powder-coated housing
 · Dimensions (L x W x H): approx. 341 x 162 x 98 mm



TOP FRAME **RAL 9006**

Asymmetrical surround frame, long – for 8-way power socket
 925.501 | · Aluminium flap RAL 9006, black powder-coated housing
 · Dimensions (L x W x H): approx. 523 x 162 x 98 mm



TOP FRAME **RAL 9006**

Symmetrical surround frame, short – for 4-way power strip
 925.800 | · Aluminium flap RAL 9006, black powder-coated housing
 · Dimensions (L x W x H): approx. 400 x 177 x 98 mm



TOP FRAME **RAL 9006**

Symmetrical surround frame, long – for 8-way power socket
 925.801 | · Aluminium flap RAL 9006, black powder-coated housing
 · Dimensions (L x W x H): approx. 583 x 177 x 98 mm



You will find power strips suitable for Slide, Conference and Top Frame on the next two pages

Power strips

See glossary for country-specific information

Supply lines and Custom Modules are available separately

Art. no. | Version



CUSTOM		4-way: 3x custom modules + power socket outlet	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
	909.002	· 1 black socket outlet with earthing contact, set at 35°	
	909.025	· 1 child-proof French / UTE socket outlet, black, set at 35°	
	909.028*	· 1 Swiss / CH socket outlet, black, set at 0°	
	909.065*	· 1 Italian / earth contact combination, black, set at 35°	



CUSTOM		4-way: 2x custom modules + power socket outlets	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
	909.003	· 2 black socket outlets with earthing contact, set at 35°	
	909.010	· 2 child-proof French / UTE socket outlets, black, set at 35°	
	909.017	· 2 Swiss / CH socket outlets, black, set at 0°	
	909.029*	· 2 Italian / earth contact combination, black, set at 35°	



CUSTOM		4-way: 1x custom module + power socket outlets	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
	909.004	· 3 black socket outlets with earthing contact, set at 35°	
	909.011	· 3 child-proof French / UTE socket outlets, black, set at 35°	
	909.018	· 4 Swiss / CH socket outlets, black, set at 0°	
	909.058*	· 3 Italian / earth contact combination, black, set at 35°	
	909.021	· 2 UK 5A individually fused, child-proof 90°	

























CUSTOM		4-way: 4x custom modules	Length: approx. 260 mm
Anodised aluminium profile; without power connection			
	909.000	· without socket outlets	

Power strips

See glossary for country-specific information

Supply lines and Custom Modules are available separately

Art. no.	Version		
8-way: 6x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.005	· 2 black socket outlet with earthing contact, set at 35°		
909.012	· 2 child-proof French / UTE socket outlet, black, set at 35°		
909.033*	· 2 Swiss / CH socket outlet, black, set at 0°		
8-way: 5x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.006	· 3 black socket outlet with earthing contact, set at 35°		
909.013	· 3 child-proof French / UTE socket outlet, black, set at 35°		
909.023*	· 2 UK 5A individually fused, child-proof 90°		
8-way: 4x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.007	· 4 black socket outlet with earthing contact, set at 35°		
909.014	· 4 child-proof French / UTE socket outlet, black, set at 35°		
909.019	· 5 Swiss / CH socket outlets, black, set at 0°		
909.050*	· 4 Italian / earth contact combination, black, set at 35°		
8-way: 3x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.008	· 5 black socket outlet with earthing contact, set at 35°		
909.015	· 5 child-proof French / UTE socket outlet, black, set at 35°		
909.020	· 6 Swiss / CH socket outlets, black, set at 0°		
909.022*	· 4 UK 5A individually fused, child-proof 90°		
8-way: 2x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.009	· 6 black socket outlet with earthing contact, set at 35°		
909.016	· 6 child-proof French / UTE socket outlet, black, set at 35°		
8-way: 8x custom modules		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; without power connection			
909.001	· without socket outlets		

CONFERENCE guide rail set

Art. no.	Version
CONFERENCE guide rail set	
For power strips (pages 18 – 19)	
940.099	· Guide rail, plastic, black · Incl. 2 countersunk head screws 2.9 x 13 mm with torx to DIN 7982

