GREDA



80

3730V Moccasin (LRV - Y10.37)



6755V Electric Azure (LRV - Y3.77)



8773V Livid Grey (LRV - Y10.40)



1763V Crackled Station

(LRV - Y12.20)

5761V Lime Spring (LRV - Y24.37)



8775V Ghost Machine (LRV - Y4.19)

Style 1/12th Gauge

Yarn Construction 100% Solution Dyed Nylon

Pile Yarn Weight 750 gsm
Pile Height 3mm - 6.5mm

Total Weight 4,570 gsm for Envirobase

Total Thickness 4,570 gsm for Envirobase

Backing 100% Envirobase - minimum of 75% recycled material

100% Komfort Bac available on request

Dimensions50cm x 50cmWear ClassificationHeavy Contract

Luxury Class LC

Additional Backing

Anti-static < 2kV body voltage.

Suitable for use with computers

Colour Fastness To Light (ISO105 – BO2) > 5

To Water (ISO 105 - E01) > 4

To Rubbing (ISO 105 - X12) > 4

Flammability Floorcoverings tested to BS4790

(Hot Metal Nut Test)

Low Radius of Char BFI-s1

Castor Chair Test BS EN 985 r value 2.8 continuous use

Warranty 10 Year Warranty

Voc Content E1 in relation to EN 14041:2004

81

